



### Key Features

- Operates in extreme environments
- Simple installation - between wall studs
- Advanced electronic control system
- Liquid bottle probe
- Humidity control
- Energy saving mode
- Fully ductable
- 55°F temperature differential

**MSRP \$3,465**

### Features

The Extreme Platinum Series is WhisperKOOL's most advanced and powerful self-contained cooling unit. The Extreme is designed to fit between standard wall studs for simple "through-the-wall" installation with minimum modification to existing wall structures. Extremes are acceptable for mounting through an exterior wall and can operate in a 110°F exhaust environment. The unit is equipped with our Platinum Series controller utilizing Advanced System Protection Technology. This features a series of strategically placed monitoring probes, which insure efficient performance and long cooling unit life. The controller is easy to operate and has features such as adjustable humidity control, energy saving modes, quick chill mode and anti-frost function.

### Specifications

Cellar Size	1000 cu. ft.
Dimensions	14.25"W x 15.75"H x 25.5"D
Weight	85lbs
AMPS (starting/running)	32/9
Installation	Through-the-Wall, partially ducted, fully ducted
Thermostat	Digital Control Display
Temp. Delta	55°F temperature differential (maintains proper cellar temperature when exhaust environment does not exceed 110°F)
Outside Venting	Can be done if the outside temperature does not exceed 110°F, the external grille cover is highly recommended.
Ducting Options	Unit can be fully ducted.
Warranty	2 year parts and labor / 5 year compressor

### Optional Accessories

Ducting Plenum, Exterior Grille



[Owner's Manual](#)



[Video Demo](#)



### Key Features

- Variable speed fans
- Simple installation - between wall studs
- Advanced electronic control system
- Liquid bottle probe
- Humidity control
- Energy saving mode
- Fully ductable
- 55°F temperature differential

**MSRP \$3,995**

### Features

The Extreme 8000ti introduces variable speed fans to WhisperKOOL's most advanced and powerful self-contained cooling system. Utilizing variable speed fans this high capacity unit can maintain optimal cellar conditions while operating at a quiet 57 decibels. The Extreme is designed to fit between standard wall studs for simple "through-the-wall" installation with minimum modification to existing wall structures. Extremes are acceptable for mounting through an exterior wall and can operate in a 110°F exhaust environment. The 8000ti includes our most advanced controller utilizing Advanced System Protection Technology. This features a series of strategically placed monitoring probes, which insure efficient performance and long cooling unit life. This system is designed to maintain 55°F and 50-70% relative humidity in a cellar up to 2000cu. ft. in size.

### Specifications

Cellar Size	up to 2000 cu. ft.
Dimensions	14.25"W x 22.5"H x 27.5"D
Weight	110lbs
AMPS (starting/running)	36/10
Installation	Through-the-Wall, partially ducted, fully ducted
Thermostat	Digital Control Display
Temp. Delta	55°F temperature differential (maintains proper cellar temperature when exhaust environment does not exceed 110°F)
Outside Venting	Can be done if the outside temperature does not exceed 110°F, the external grille cover is highly recommended.
Ducting Options	Unit can be fully ducted.
Warranty	2 year parts and labor / 5 year compressor

### Optional Accessories

Ducting Plenum, Exterior Grille



Owner's Manual



Video Demo