



### Key Features

- Noise-free cellar environment
- Operates in extreme environments
- Simple installation - between wall studs
- Remote Advanced electronic control system w/ 50ft. communication line
- Liquid bottle probe
- Humidity control
- Energy saving mode
- 55°F temperature differential

**4000 MSRP \$5,135**  
**8000ti MSRP \$5,795**

### Features

The Fully Ducted Extreme Series units can be positioned up to 25 ducted feet from the cellar, creating a noise-free cellar environment. Fully ducted installation provides many installation options, allowing you to not only put the unit in more remote areas of the home but to also have full control of where the exhaust air vents to. The unit is equipped with our Remote Platinum Series controller (which can be placed up to 300 line feet from the unit) utilizing Advanced System Protection Technology. This features a series of strategically placed monitoring probes, which insure efficient performance and long cooling unit life. The controller is easy to operate and has features such as adjustable humidity control, energy saving modes, quick chill mode and anti-frost function.

### Specifications

Model	4000	8000ti
Cellar Size	1000 cu. ft.	2000 cu. ft.
Dimensions	14.25"W x 15.75"H x 25.5"D	14.25"W x 22.5"H x 27.5"D
Weight	85lbs	110lbs
AMPS (starting/running)	32/9	36/10
Installation	Within 25 ducted feet of cellar.	
Thermostat	Digital Control Display	
Temp. Delta	55°F temperature differential (maintains proper cellar temperature when exhaust environment does not exceed 110°F)	
Outside Venting	Can be done if the outside temperature does not exceed 110°F, the external grille cover is highly recommended.	
Warranty	2 year parts and labor / 5 year compressor	

### Optional Accessories

Ducting Plenum, Exterior Grille



Owner's Manual



Video Demo